



Series	Model Number	CFM	CFH (3500 RPM)	Nominal HP	Max PSI LS/HS (1)	Min/ Max Speed (Hz)	Max Saturated Suction Temperature ⁽²⁾ (°F)					CR Type	CR Range	IQ Module ⁽³⁾	Oil Charge (Gallons)	Weight (lbs)	SL Conn. Type	SL (in)	DL Conn. Type	DL (in)
							R134a	R404A	R407C	R407A/F	R22									
CSH85	CSH 6563-35Y	97	5830	35	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	2.6	692	Ser. Vlv	2 1/8	Ser. Vlv	1 5/8
CSH85	CSH 6563-50(Y)	97	5830	50	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	2.6	717	Ser. Vlv	2 1/8	Ser. Vlv	1 5/8
CSH85	CSH 6563-40Y	121	7244	40	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	2.6	699	Ser. Vlv	2 1/8	Ser. Vlv	1 5/8
CSH85	CSH 6563-60(Y)	121	7244	60	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	2.6	717	Ser. Vlv	2 1/8	Ser. Vlv	1 5/8
CSH85	CSH 6583-50Y	138	8299	50	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	2.6	810	Ser. Vlv	2 5/8	Ser. Vlv	2 1/8
CSH85	CSH 6593-60Y	155	9323	60	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	2.6	810	Ser. Vlv	2 5/8	Ser. Vlv	2 1/8
CSH75	CSH 7563-50Y	140	8410	50	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1114	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7563-70(Y)	140	8410	70	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	4.1	1147	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7563-60Y	161	9682	60	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1136	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7563-80(Y)	161	9682	80	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	4.1	1158	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7573-70Y	183	10989	70	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1147	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7573-90(Y)	183	10989	90	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	4.1	1180	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7583-80Y	210	12572	80	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1169	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7583-100(Y)	210	12572	100	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	4.1	1191	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7593-90Y	239	14338	90	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1180	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH75	CSH 7593-110(Y)	239	14338	110	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	4.1	1224	Ser. Vlv	3 1/8	Ser. Vlv	2 1/8
CSH85	CSH 8563-80Y	224	13428	80	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	6.0	1852	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8563-110(Y)	224	13428	110	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	6.0	1874	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8563-90Y	255	15300	90	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	6.0	1852	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8563-125(Y)	255	15300	125	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	6.0	1896	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8573-110Y	292	17491	110	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	6.0	1874	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8573-140(Y)	292	17491	140	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	6.0	1918	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8583-125Y	334	20024	125	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	5.2	1896	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8583-160Y	334	20024	160	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	5.2	1910	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8593-140Y	377	22602	140	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	5.2	1918	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH85	CSH 8593-180(Y)	377	22602	180	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	5.2	1962	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH95	CSH 9563-180(Y)	380	22802	180	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	8.2	2844	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH95	CSH 9563-160Y	437	26212	160	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	2822	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH95	CSH 9563-210(Y)	437	26212	210	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	8.2	2889	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH95	CSH 9573-180Y	497	29835	180	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	2844	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH95	CSH 9573-240(Y)	497	29835	240	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	8.2	2911	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSH95	CSH 9583-210Y	572	34310	210	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	2977	Bushing	5	Ser. Vlv	4 1/8
CSH95	CSH 9583-280(Y)	572	34310	280	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	8.2	3034	Bushing	5	Ser. Vlv	4 1/8
CSH95	CSH 9593-240Y	646	38786	240	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	3022	Bushing	5	Ser. Vlv	4 1/8
CSH95	CSH 9593-300(Y)	646	38786	300	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	8.2	3087	Bushing	5	Ser. Vlv	4 1/8
CSH95	CSH 95103-280Y	721	43261	280	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.8	3219	Bushing	5	Ser. Vlv	4 1/8
CSH95	CSH 95103-320(Y)	597	43261	320	275 / 400	25-60	+77	+32	+55	+32	+55	Slide Valve	25-100%	SE-11	8.8	3308	Bushing	5	Ser. Vlv	4 1/8
CSH95	CSH 95113-320Y	795	47710	320	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.8	3308	Bushing	5	Ser. Vlv	4 1/8
Series	Model Number	CFM	CFH (3500 RPM)	Nominal HP	Max PSI LS/HS (1)	Min/ Max Speed (Hz)	Max Saturated Suction Temperature ⁽²⁾ (°F)					CR Type	CR Range	IQ Module ⁽³⁾	Oil Charge (Gallons)	Weight (lbs)	SL Conn. Type	SL (in)	DL Conn. Type	DL (in)
CSW65	CSW 6563-40Y	139	8311	40	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	2.8	805	Ser. Vlv	2 5/8	Ser. Vlv	2 1/8
CSW65	CSW 6563-50(Y)	139	8311	50	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	2.8	805	Ser. Vlv	2 5/8	Ser. Vlv	2 1/8
CSW65	CSW 6593-50Y	156	9377	50	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	2.8	805	Ser. Vlv	2 5/8	Ser. Vlv	2 1/8
CSW65	CSW 6593-60(Y)	156	9377	60	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	2.8	805	Ser. Vlv	2 5/8	Ser. Vlv	2 1/8
CSW75	CSW 7573-60Y	183	10989	60	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1147	Ser. Vlv	3 1/8	Ser. Vlv	2 5/8
CSW75	CSW 7573-70(Y)	183	10989	70	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	4.1	1147	Ser. Vlv	3 1/8	Ser. Vlv	2 5/8
CSW75	CSW 7583-70Y	210	12572	70	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1169	Ser. Vlv	3 1/8	Ser. Vlv	2 5/8
CSW75	CSW 7583-80(Y)	210	12572	80	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	4.1	1169	Ser. Vlv	3 1/8	Ser. Vlv	2 5/8
CSW75	CSW 7593-80Y	239	14321	80	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	4.1	1180	Ser. Vlv	3 1/8	Ser. Vlv	2 5/8
CSW75	CSW 7593-90(Y)	239	14321	90	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	4.1	1180	Ser. Vlv	3 1/8	Ser. Vlv	2 5/8
CSW85	CSW 8573-90Y	292	17491	90	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	6.0	1874	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSW85	CSW 8573-110(Y)	292	17491	110	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	6.0	1874	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSW85	CSW 8583-110Y	334	20035	110	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	5.2	1896	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSW85	CSW 8583-125(Y)	334	20035	125	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	5.2	1896	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSW85	CSW 8593-125Y	380	22802	125	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	5.2	1918	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSW85	CSW 8593-140(Y)	380	22802	140	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	5.2	1918	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8
CSW95	CSW 9563-140Y	437	26219	140	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	2822	Ser. Vlv	4 1/8	Ser. Vlv	4 1/8
CSW95	CSW 9563-160(Y)	437	26219	160	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	8.2	2822	Ser. Vlv	4 1/8	Ser. Vlv	4 1/8
CSW95	CSW 9573-160Y	497	29835	160	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	2844	Ser. Vlv	4 1/8	Ser. Vlv	4 1/8
CSW95	CSW 9573-180(Y)	497	29835	180	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	8.2	2844	Ser. Vlv	4 1/8	Ser. Vlv	4 1/8
CSW95	CSW 9583-180Y	572	34310	180	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	2977	Bushing	5	Ser. Vlv	4 1/8
CSW95	CSW 9583-210(Y)	572	34310	210	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	8.2	3021	Bushing	5	Ser. Vlv	4 1/8
CSW95	CSW 9593-210Y	646	38785	210	275 / 400	25-60	+55	--	--	--	--	Slide Valve	25-100%	SE-11	8.2	3020	Bushing	5	Ser. Vlv	4 1/8
CSW95	CSW 9593-240(Y)	646	38785	240	275 / 400	25-60	+77	--	+55	--	+55	Slide Valve	25-100%	SE-11	8.2	3043	Bushing	5	Ser. Vlv	4 1/8



Series	Model Number	CFM	CFH (3500 RPM)	Nominal HP	Max PSI LS/HS (1)	Min/ Max Speed (Hz)	Max Saturated Suction Temperature ⁽²⁾ (°F)					CR Type	CR Range	IQ Module ⁽³⁾	Weight (lbs)	SL Conn. Type	SL (in)	DL Conn. Type	DL (in)	
							R134a	R404A,R448/9A,R407A/F	R	R407C	R22									
HS.53	HSN 5343-20	59	3540	20	275 / 400	20-75	--	+5	--	+14	Step	100-85-55%	SE-11	366	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.53	HSK 5343-30	59	3540	30	275 / 400	20-75	--	+5	+55	+14	Step	100-90-70%	SE-11	400	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.53	HSN 5353-25	71	4260	25	275 / 400	20-75	--	+5	--	+14	Step	100-80-45%	SE-11	373	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.53	HSK 5353-35	71	4260	35	275 / 400	20-75	--	+5	+55	+14	Step	100-85-60%	SE-11	392	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.53	HSN 5363-30	84	5040	30	275 / 400	20-75	--	+5	--	+14	Step	100-70-40%	SE-11	384	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.53	HSK 5363-40	84	5040	40	275 / 400	20-75	--	+5	+55	+14	Step	100-75-50%	SE-11	404	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.64	HSN 6451-40	99	5940	40	275 / 400	20-75	--	+5	--	+14	Step	100-75-50%	SE-11	516	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.64	HSK 6451-50	99	5940	50	275 / 400	20-75	--	+5	+55	+14	Step	100-75-50%	SE-11	525	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.64	HSN 6461-50	117	7020	50	275 / 400	20-75	--	+5	--	+14	Step	100-75-50%	SE-11	525	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.64	HSK 6461-60	117	7020	60	275 / 400	20-75	--	+5	+55	+14	Step	100-75-50%	SE-11	542	Ser. Vlv	2 1/8	Bushing	1 5/8		
HS.74	HSN 7451-60	137	8220	60	275 / 400	20-75	--	+5	--	+14	Step	100-75-50%	SE-11	655	Ser. Vlv	3 1/8	Bushing	2 1/8		
HS.74	HSK 7451-70	137	8220	70	275 / 400	20-75	--	+5	+55	+14	Step	100-75-50%	SE-11	673	Ser. Vlv	3 1/8	Bushing	2 1/8		
HS.74	HSN 7461-70	157	9420	70	275 / 400	20-75	--	+5	--	+14	Step	100-75-50%	SE-11	684	Ser. Vlv	3 1/8	Bushing	2 1/8		
HS.74	HSK 7461-80	157	9420	80	275 / 400	20-75	--	+5	+55	+14	Step	100-75-50%	SE-11	692	Ser. Vlv	3 1/8	Bushing	2 1/8		
HS.74	HSN 7471-75	178	10680	75	275 / 400	20-75	--	+5	--	+14	Step	100-75-50%	SE-11	719	Ser. Vlv	3 1/8	Bushing	2 1/8		
HS.74	HSK 7471-90	178	10680	90	275 / 400	20-75	--	+5	+55	+14	Step	100-75-50%	SE-11	741	Ser. Vlv	3 1/8	Bushing	2 1/8		
HS.85	HSK 8561-110	224	13428	110	275 / 400	20-75	--	+5	+55	+14	Slide Valve	50-100%	SE-11, CM-SW	1246	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSN 8561-110	255	15300	110	275 / 400	20-75	--	+5	--	+14	Slide Valve	50-100%	SE-11, CM-SW	1246	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSK 8561-125	255	15300	125	275 / 400	20-75	--	+5	+55	+14	Slide Valve	50-100%	SE-11, CM-SW	1279	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSN 8571-125	292	17491	125	275 / 400	20-75	--	+5	--	+14	Slide Valve	50-100%	SE-11, CM-SW	1345	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSK 8571-140	292	17491	140	275 / 400	20-75	--	+5	+55	+14	Slide Valve	50-100%	SE-11, CM-SW	1279	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSK 8581-160	334	20024	160	275 / 400	20-75	--	+5	+55	+14	Slide Valve	50-100%	SE-11, CM-SW	1374	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSN 8591-160	378	22672	160	275 / 400	20-75	--	+5	--	+14	Slide Valve	50-100%	SE-11, CM-SW	1499	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
HS.85	HSK 8591-180	377	22602	180	275 / 400	20-75	--	+5	+55	+14	Slide Valve	50-100%	SE-11, CM-SW	1290	Ser. Vlv	4 1/8	Ser. Vlv	3 1/8		
Series	Model Number	CFM	CFH (3500 RPM)	Rotation	Max PSI LS/HS (1)	Min/ Max Speed (rpm)	Max Saturated Suction Temperature ⁽²⁾ (°F)					CR Type	CR Range	IQ Module ⁽³⁾	Weight (lbs)	SL Conn. Type	SL (in)	DL Conn. Type	DL (in)	
						R134a	R404A	R407A/F	R407C	R22										
OS.53	OSK 5341	59	3540	CW	275 / 400	1450 - 4500	--	+5	+45	+55	+55	Step	100-75%	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8	
OS.53	OSN 5351	71	4260	CW	275 / 400	1450 - 4500	--	+5	+5	--	+14	Step	100-75%	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8	
OS.53	OSK 5351	71	4260	CW	275 / 400	1450 - 4500	--	+5	+45	+55	+55	Step	100-75%	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8	
OS.53	OSN 5361	84	5040	CW	275 / 400	1450 - 4500	--	+5	+5	--	+14	Step	100-75%	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8	
OS.53	OSK 5361	84	5040	CW	275 / 400	1450 - 4500	--	+5	+45	+55	+55	Step	100-75%	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8	
OS.74	OSN 7441	117	7020	CCW	275 / 400	1450 - 4000	--	+5	+5	--	+14	Step	100-75%	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSK 7441	117	7020	CCW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Step	100-75%	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSN 7451	137	8220	CCW	275 / 400	1450 - 4000	--	+5	+5	--	+14	Step	100-75%	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSK 7451	137	8220	CCW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Step	100-75%	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSN 7461	157	9420	CCW	275 / 400	1450 - 4000	--	+5	+5	--	+14	Step	100-75%	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSK 7461	157	9420	CCW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Step	100-75%	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSN 7471	178	10680	CCW	275 / 400	1450 - 4000	--	+5	+5	--	+14	Step	100-75%	--	415	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.74	OSK 7471	178	10680	CCW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Step	100-75%	--	415	Ser. Vlv	3 1/8	Bushing	2 1/8	
OS.85	OSK 8551	224	13426	CW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Slide Valve	50-100%	CM-SW	728	Ser. Vlv	4 1/8	Bushing	3 1/8	
OS.85	OSK 8561	255	15301	CW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Slide Valve	50-100%	CM-SW	750	Ser. Vlv	4 1/8	Bushing	3 1/8	
OS.85	OSN 8571	291	17475	CW	275 / 400	1450 - 4000	--	+5	+5	--	+14	Slide Valve	50-100%	CM-SW	772	Ser. Vlv	4 1/8	Bushing	3 1/8	
OS.85	OSK 8571	291	17475	CW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Slide Valve	50-100%	CM-SW	772	Ser. Vlv	4 1/8	Bushing	3 1/8	
OS.85	OSK 8581	334	20020	CW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Slide Valve	50-100%	CM-SW	728	Ser. Vlv	4 1/8	Bushing	3 1/8	
OS.85	OSK 8591	377	22600	CW	275 / 400	1450 - 4000	--	+5	+45	+55	+55	Slide Valve	50-100%	CM-SW	790	Ser. Vlv	4 1/8	Bushing	3 1/8	
OS.85	OSN 8591	377	22600	CW	275 / 400	1450 - 4000	--	+5	+5	--	+14	Slide Valve	50-100%	CM-SW	790	Ser. Vlv	4 1/8	Bushing	3 1/8	
Series	Model Number	CFM	CFH (3500 RPM)	Rotation	Max PSI LS/HS (1)	Min/ Max Speed (rpm)	SST ⁽²⁾ (°F)					CR Type	CR Range	IQ Module ⁽³⁾	Variable Vi	Weight (lbs)	SL Conn. Type	SL (in)	DL Conn. Type	DL (in)
						Min	Max													
OSA.53	OSKA 5341	59	3540	CW	275 / 400	1450 - 4500	-4	+54				Step	100-75%	--	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8
OSA.53	OSNA 5351	71	4260	CW	275 / 400	1450 - 4500	-49	+14				Step	100-75%	--	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8
OSA.53	OSKA 5351	71	4260	CW	275 / 400	1450 - 4500	-4	+54				Step	100-75%	--	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8
OSA.53	OSNA 5361	84	5040	CW	275 / 400	1450 - 4500	-49	+14				Step	100-75%	--	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8
OSA.53	OSKA 5361	84	5040	CW	275 / 400	1450 - 4500	-4	+54				Step	100-75%	--	--	143	Ser. Vlv	2 1/8	Bushing	1 5/8
OSA.74	OSHA 7452	137	8220	CCW	275 / 400	1450 - 4000	+23	+77				Step	100-75-50%	--	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSKA 7452	137	8220	CCW	275 / 400	1450 - 4000	-4	+54				Step	100-75-50%	--	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSNA 7452	137	8220	CCW	275 / 400	1450 - 4000	-49	+14				Step	100-75-50%	--	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSHA 7462	157	9420	CCW	275 / 400	1450 - 4000	+23	+77				Step	100-75-50%	--	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSKA 7462	157	9420	CCW	275 / 400	1450 - 4000	-4	+54				Step	100-75-50%	--	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSNA 7462	157	9420	CCW	275 / 400	1450 - 4000	-49	+14				Step	100-75-50%	--	--	388	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSHA 7472	178	10680	CCW	275 / 400	1450 - 4000	+23	+77				Step	100-75-50%	--	--	415	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSKA 7472	178	10680	CCW	275 / 400	1450 - 4000	-4	+54				Step	100-75-50%	--	--	415	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.74	OSNA 7472	178	10680	CCW	275 / 400	1450 - 4000	-49	+14				Step	100-75-50%	--	--	415	Ser. Vlv	3 1/8	Bushing	2 1/8
OSA.85	OSKA 8551	224	13426	CW	275 / 400	1450 - 4000	-4	+54				Slide Valve	50-100%	CM-SW	--	728	Bushing	4 1/8	Bushing	3 1/8
OSA.85	OSKA 8561	255	15301	CW	275 / 400	1450 - 4000	-4	+54				Slide Valve	50-100%	CM-SW	--	750	Bushing	4 1/8	Bushing	3 1/8
OSA.85	OSNA 8571	291	17475	CW	275 / 400	1450 - 4000	-49	+14				Slide Valve	50-100%	CM-SW	--	772	Bushing	4 1/8	Bushing	3 1/8
OSA.85	OSKA 8571	291	17475	CW	275 / 400	1450 - 4000	-4	+54				Slide Valve	50-100%	CM-SW	--	772	Bushing	4 1/8	Bushing	3 1/8
OSA.85	OSKA 8581	334	20020	CW	275 / 400	1450 - 4000	-4	+54				Slide Valve	50-100%	CM-SW	--	790	Bushing	4 1/8	Bushing	3 1/8
OSA.85	OSNA 8591	377	22600	CW	275 / 400	1450 - 4000	-49	+14				Slide Valve	50-100%	CM-SW	--	790	Bushing	4 1/8	Bushing	3 1/8
OSA.85	OSKA 8591	377	22600	CW	275 / 400	1450 - 4000	-4	+54				Slide Valve	50-100%	CM-SW	--	790	Bushing	4 1/8	Bushing	3 1/8
OSA.95	OSKA 9573	497	29835																	