

	Model Number 460V ONLY	APPLICATION	Rated Input Current (480V)	Max Fuse Size	CRC-0061-VS September-17
Ecoline					Ecoline
CE2	**<i>(2DES-3.F1Y-4SU)</i>**	<i>Not Available</i>	12	25	CE2
	2DES-3.F3Y-4SU		27.7	30	
CE3	**<i>(4FES-5.F1Y-4SU)</i>**	<i>Not Available</i>	12	25	CE3
	4FES-5.F3Y-4SU		27.7	30	
	<i>(4EES-6.F1Y-4SU)</i>	<i>Not Available</i>	12	25	
	4EES-6.F3Y-4SU		27.7	30	
	4DES-7.F3Y-4SU		27.7	30	
	4CES-9.F3Y-4SU		27.7	30	
CE4	4VES-7.F3Y-2NU	R134a ONLY	27.7	30	CE4
	4VES-10.F4Y-2NU		47.6	60	
	4TES-9.F3Y-2NU	R134a ONLY	27.7	30	
	4TES-12.F4Y-2NU		47.6	60	
	4PES-12.F3Y-2NU	R134a ONLY	27.7	30	
	4PES-15.F4Y-2NU		47.6	60	
	4NES-14.F3Y-2NU	R134a ONLY	27.7	30	
	4NES-20.F4Y-2NU		47.6	60	
CO2 Transcritical					CO2 Transcritical
CKH3	4PTC-7.F3K-23DU		27.7	30	CKH3
	4MTC-10.F4K-23DU		47.6	60	
	4KTC-10.F4K-23DU		47.6	60	

Fuse type must be fast acting and UL approved.
 --Must use Class CC for up to 30 Amps.
 --Must use Class J for 30 amps to 60 amps