

		Rated Input Current (460V)	*Recommended Fuse Size (Amps)	*Max Fuse Size (Amps)	Speed Range (RPM)	Rated Supply Voltage	CRC-0061-CSVH Sep-26	
CSVH	CSVH24-125Y-4AU	190	250	400	1200-5120	440-480	CSVH24-125Y-4AU	CSVH
	CSVH25-160Y-4AU	225	315	400	1200-6400	440-480	CSVH25-160Y-4AU	
	CSVH26-200Y-4AU	290	350	400	1200-8000	440-480	CSVH26-200Y-4AU	
	CSVH37-240Y-4AU	370	450	600	1200-5310	440-480	CSVH37-240Y-4AU	
	CSVH38-290Y-4AU	430	500	600	1200-6400	440-480	CSVH38-290Y-4AU	
CSVH	CSVH24-125MY-4MU	190	250	400	1200-5120	440-480	CSVH24-125MY-4MU	CSVH
	CSVH25-160MY-4MU	225	315	400	1200-6400	440-480	CSVH25-160MY-4MU	
	CSVH26-200MY-4MU	290	350	400	1200-8000	440-480	CSVH26-200MY-4MU	
CSVW	CSVW24-125Y-4AU	190	250	400	1200-5120	440-480	CSVW24-125Y-4AU	CSVW
	CSVW25-160Y-4AU	225	315	400	1200-6400	440-480	CSVW25-160Y-4AU	
	CSVW26-200Y-4AU	290	350	400	1200-8000	440-480	CSVW26-200Y-4AU	
	CSVW37-240Y-4AU	370	450	600	1200-5310	440-480	CSVW37-240Y-4AU	
	CSVW38-290Y-4AU	430	500	600	1200-6400	440-480	CSVW38-290Y-4AU	
CSVW	CSVW24-125MY-4MU	190	250	400	1200-5120	440-480	CSVW24-125MY-4MU	CSVW
	CSVW25-160MY-4MU	225	315	400	1200-6400	440-480	CSVW25-160MY-4MU	
	CSVW26-200MY-4MU	290	350	400	1200-8000	440-480	CSVW26-200MY-4MU	

*Fuse type must be fast acting and UL approved.

Bussmann (Type FWH)

Mersen (Type A50QS)

Littlefuse (Type L50S)