



# SALES INFORMATION

MP-0067-01 // July 2020

## UPDATES FOR STANDARD VERTICAL OIL SEPARATOR

### GENERAL

As part of our continuous product standardization and optimization process, BITZER US is increasing its flexibility to meet the market demands by implementing the following updates immediately.

### SIGHT GLASSES

- The number of sight glasses will increase from two to three
- The third sight glass is located at the same height as low level switch
- AWA sight glasses are now used to standardize across all our oil separators
- Sight glasses can be removed and replaced with an OLC-D1 Optoelectronic Eye Kit (order separately).



### SKIRT

- Oil separator will use standard skirts
- Skirts have more anchoring holes and is consistent with other vertical design

The table below lists changes to dimensions:

Oil Separator	Inlet Height (Previous)	Inlet Height (Current)	Oil Outlet Height (Previous)	Oil Outlet Height (Current)	Overall Height (Previous)	Overall Height (Current)
OA1954US	21-1/2	22-7/8	5-7/8	6-1/4	31	31-3/8
OA4188US	30-1/2	30-7/8	7-7/8	8-1/4	41-13/16	42-3/16
OA9111US	42-1/2	42-7/8	10-3/8	10-3/4	56-1/8	56-9/16
OA14111US	43-1/8	44	12-1/4	13-1/8	58-7/8	59-3/4
OA25112US	-	-	-	-	70-1/4	69-1/4

Notes:

1. “-“ indicates no changes made
2. All dimensions are in inches

Approval drawings will be provided upon request